Ingersoll Rand®

2235QXPA

1/2″ Impactool™



REAL TOOLS FOR REAL WORK.℠

Powered by legend.

The 2235QXPA 1/2″ Impactool™

Super powerful, ultra durable and with that extra bit of comfort: Succeeding the legendary Thunder Gun racing tool, our brand new 2235QXPA is the racehorse you can bet on when the going gets tough. Designed after its successful predecessor, the new impact wrench brings the superior ergonomical advances of the race track right to your garage. And when push comes to shove, the 2235QXPA is just what you need, so you can be certain: it gets REAL WORK done right, every time.



Vehicle Service

POWER
With 1,760 Nm. of nut-busting torque and 1,220 Nm. of max reverse torque, the new 2235QXPA has the punch you need for whatever bolt gets in the way. And thanks to Ingersoll Rand's finely tuned twin-hammer impact mechanism, any tire or engine job gets done more quickly and more silently than with any other tools in its class.



DURABILITY
Born from race mechanics' legendary secret weapon, the 2235QXPA pushes the boundaries of toughness while others are already pushing the daisies. An aluminum hammercase, steel-wear plate and composite housing protect the successor of the famed Thunder Gun ½″ impact wrench from even the harshest environments.

COMFORT
Providing outstanding comfort, the impactool® is certain to not let long workdays take their toll on you. The 2235QXPA builds on a rich heritage and years of experience in the racing circuits. Its ergonomic design, its components and functions have been pushed even further making for outstanding performance which goes hand in hand with superior comfort.

WEIGHT
Weighing in at only 2.1 kg, the new ½″ impactool® is the perfect partner to work harder and faster with for longer stretches of time – so you can finish off REAL WORK with less weighing you down.

Specifications

Model	CPN	Drive Size, Type	Max Reverse Torque Nm	Nut-Busting Torque Nm	BPM	Free Speed (rpm)	Weight lb (kg)	Length in. (mm)	Sound Level dB(A)
2235 Series Impactool™									
2235QXPA	47532836001	1/2″	1220	1760	1220	8500	2.10	193	88.7

Performance at 90 PSI (6,2 bar). Air inlet NPTF 1/4″ (6mm).
Min hose size 3/8″ (10mm). Average air consumption 6.0 cfm (170 l/min) – at load 24 cfm (680 l/min).

Ingersoll Rand

download.irtool.eu
REAL TOOLS FOR REAL WORK.

Ingersoll Rand (NYSE:IR) advances the quality of life by creating and sustaining comfortable and efficient environments. Our people and our family of brands — including Club Car®, Ingersoll Rand®, Thermo King® and Trane® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a $12 billion global business committed to a world of sustainable progress and enduring results.

©2014 Ingersoll Rand IRITS-0815-129 EUEN