Ingersoll Rand®

# Ultra-Compact Impact Wrench

## 36QMAX & 15QMAX




REAL TOOLS FOR REAL WORK™

# Ultra Power – Ultra Compact – Ultra Reliable

## Ingersoll Rand® 36QMAX ½" & 15QMAX ⅜" Ultra-Compact Impact Wrenches

Introducing the Ingersoll Rand® 36QMAX Quiet Ultra-Compact Impact Wrench. Built on Ingersoll Rand's 100-year legacy developing industry leading tools, you can always rely on the 36QMAX. This tool has been rigorously tested, beaten up, dropped and pushed to the limits to make sure it lasts **twice as long as the competition**. With their twin hammer design, unmatched durability, superior accessibility and up to 640 ft-lbs* of nut busting torque at just 2.4 lbs, the 36QMAX and 15QMAX are not just tools you want, they are tools you need to get REAL WORK done time and time again.


Suspension


Engine Bay


Wheel Lugs


Subframe bolts

## Tool Features

**ACCESS**
There is no place for work to hide; as this compact design gives the user the access and power they need, even if the task is up, under, over, or around any awaiting obstruction.

**POWER-TO-WEIGHT**
At 2.4 pounds this tool still manages to produce 640 ft-lbs of nut busting torque making it a power-to-weight leader in its class.



**RELIABILITY**
Built on the IR Impact Wrench legacy, this tool is testing at 2X the life of competitive products available today. Backed by a 2-year warranty to prove it.

**CONTROL**
The one-handed forward/reverse push button and 3-mode power regulator give you max control and max performance.

## Specs

| Model | Drive Size, Type | Max Torque ft.-lb. (Nm) | Nut-Busting Torque ft.-lb. (Nm) | BPM | Free Speed (rpm) | Weight lb (kg) | Length in. (mm) | Sound Level dB(A) |
|---|---|---|---|---|---|---|---|---|
| 36QMAX | 1/2" | 470 (640) | 640 (870) | 1300 | 8000 | 2.4 (1.1) | 4.6 (117) | 91.3 |
| 15QMAX* | 3/8" | 380 (520) | 475 (650) | 1350 | 6000 | 2.4 (1.1) | 4.6 (117) | 89.7 |

** 36QMAX boasts 640 ft-lbs nut busting torque. 15QMAX sports 475 ft-lbs nut busting torque.*
*Performance at 6,2 bar (90 PSI) – Air inlet NPTF 1/4" (6 mm). Min hose size 3/8" (10 mm) Min hose size 3/8" (10 mm).*

2 YEAR WARRANTY

Ingersoll Rand

www.ingersollrand.com

Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is committed to helping make life better. We provide innovative and mission-critical industrial, energy, medical and specialty vehicle products and services across 40+ respected brands designed to excel in even the most complex and harsh conditions where downtime is especially costly. Our employees connect to customers for life by delivering proven expertise, productivity and efficiency improvements.

We are committed to using environmentally conscious print practices.
©2020 Ingersoll Rand IRITS-0320-011