













P=COMPRESSED AIR CONNECTION R=EXHAUST U=VACUUM CONNECTION


Item		M 10 SSX			M 14 SSX			M 18 SSX		
Intake air flow rate	m³/h	7.7	8.5	9.4	10.2	11.5	12.6	14.8	16.5	18.0
Maximum level of vacuum	-KPa	62	82	85	62	82	85	62	82	85
Final pressure	mbar abs.	380	180	150	380	180	150	380	180	150
Supply pressure	bar	3	4	5	3	4	5	3	4	5
Optimal supply pressure	bar			5			5			5
Air consumption	Nl/s	1.2	1.6	1.9	1.7	2.1	2.5	2.3	2.9	3.6
Operating temperature	°C			-10 / +80			-10 / +80			-10 / +80
Noise level at optimal supply pressure	dB(A)			60			62			66
Weight	g			144			145			150
A				34.5			34.5			44.5
B				20			20			30
C				4.5			4.5			4.5
E	Ø			29			29			35
G	Ø			G3/8"			G3/8"			G1/2"
H				106.5			106.5			136.5

Spare parts		M 10 SSX	M 14 SSX	M 18 SSX
Silencer	item	SSX 3/8"	SSX 3/8"	SSX 1/2"
Exhaust silencer	item	N°2 00 15 150	N°2 00 15 150	N°3 00 15 150
Sealing kit and reed valves	item	00 KIT M 10	00 KIT M 14	00 KIT M 18

Note: All vacuum values indicated in the table are valid at the normal atmospheric pressure of 1013 mbar and obtained with a constant supply pressure.
Vacuum generator supply must be carried out with non-lubricated compressed air, 5 micron filtration, in accordance with standard **ISO 8573-1 class 4**.


Transformation ratio: N (newton) = Kg x 9.81 (force of gravity) inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$ Adapters for GAS - NPT threading available on page 1.130

Air flow rate (Nl/s) at different level of vacuum (-KPa) at optimal supply pressure



Generator item	Supp. press. bar	Air consumption Nl/s	Air flow rate (Nl/s) at different levels of vacuums (-KPa) at optimal supply pressure									Max vacuum
			0	10	20	30	40	50	60	70	80	-KPa
M 10 SSX	5.0	1.9	2.61	2.00	1.55	0.80	0.64	0.50	0.29	0.19	0.09	85
M 14 SSX	5.0	2.5	3.50	2.33	1.72	1.00	0.89	0.67	0.35	0.24	0.11	85
M 18 SSX	5.0	3.6	5.00	3.50	2.78	2.02	1.02	0.75	0.44	0.30	0.14	85

Evacuation rates (ms/l = s/m³) at different levels of vacuums (-KPa) at optimal supply pressure



Generator item	Supp. press. bar	Air consumption Nl/s	Evacuation rates (ms/l= s/m³) at different levels of vacuums (-KPa) at optimal supply pressure									Max vacuum
			10	20	30	40	50	60	70	80	85	-KPa
M 10 SSX	5.0	1.9	40	93	188	371	629	918	1534	2731	3878	85
M 14 SSX	5.0	2.5	30	69	140	276	469	685	1144	2036	2892	85
M 18 SSX	5.0	3.6	21	48	98	193	327	478	799	1423	2020	85