OL7MKMS
OILPROOF COVER



Caratteristiche principali

- **Pressione fino a 425 bar**
- **Sviluppato per applicazioni ad alta pressione all'interno del braccio telescopico del tele-handler**

Main Features

- ***Working pressure up to 425 bar***
- ***Especially developed for high pressure applications inside tele-handler telescopic boom***

Caratteristiche tecniche

- **Caratteristiche tecnico-costruttive:**

Anima interna in poliestere termoplastico, rinforzo con speciale struttura multitreccia, rivestimento esterno in poliuretano antiabrasione stabilizzato ai raggi UV, resistente all'ozono ed ai microorganismi.

- **Temperature di utilizzo:**

Da -40°C a +100°C Da -40°F a +212°F.
Per fluidi a base acquosa la temperatura massima di esercizio è +70°C (+158°F).

- **Pressioni d'esercizio:**

Rapporto di sicurezza 1:4

Technical Features

- ***Technical-constructive features:***

Inner core in thermoplastic polyester, reinforcement with special multi-braid structure, outside cover in abrasion resistant polyurethane, UV-stabilized, resistant to ozone and microorganisms.

- ***Working temperatures:***

From -40°C to +100°C From -40°F to +212°F.
Max working temperature with water-based fluids is +70°C (+158°F).

- ***Working pressure:***

Safety ratio 1:4

Scheda tecnica - *Data Sheet*

CODE	inch	-dash	mm	DN	mm	inch	bar	psi	mm	inch	g/m	lbs/ft	FERRULE CODE
			ID		OD		WP		R MIN		g		
0L7MKMS5000	3/8"	-6	9.6	10	22.0	0.866	425	6164	75	2.95	505	0.339	BP380L7MKMS
0L7MKMS6000	1/2"	-8	13.0	12	26.7	1.051	325	4714	85	3.35	771	0.518	BP120L7MKMS
0L7MKMS7000	5/8"	-10	16.3	16	30.2	1.189	325	4714	95	3.74	946	0.636	BP580L7MKMS

Nota: disponibile su richiesta anche la versione con cover water proof.

Note: available on demand with water proof cover.