TUBI IN POLIURETANO BINATI BASSA PRESSIONE
LOW PRESSURE TWIN POLYURETHANE TUBES



CARATTERISTICHE TECNICHE - TUBI IN POLIURETANO BINATI BASSA PRESSIONE
TECHNICAL SPECIFICATIONS - LOW PRESSURE TWIN POLYURETHANE TUBES

Tipo tubo binato *Twin hose type*	Codice *Code*	ø Esterno *External* (mm)	ø Interno *Internal* (mm)	Press. scoppio min. *Min. burst pressure* (bar)	Press. eserc. max Max Working pressure (bar)	Raggio curv. min. *Min. Bend radius* (mm)	Peso *Weight* (g/m)
2 TUBI 4x1 BLU/NERO	MPU422	4.0	2.0	56	19	11	23
2 TUBI 4x1,25 BLU/NERO	MPU4252	4.0	2.5	40	13	15	19
2 TUBI 6x1 BLU/NERO	MPU642	6.0	4.0	40	13	18	39
2 TUBI 8x1 BLU/NERO	MPU862	8.0	6.0	28	9	35	54
2 TUBI 8x1,25 BLU/NERO	MPU8552	8.0	5.5	36	12	30	65
2 TUBI 8x1,5 BLU/NERO	MPU852	8.0	5.0	52	17	25	75

APPLICAZIONI: Le tubazioni della SERIE PU BINATO BASSA PRESSIONE grazie alla buona flessibilità e di conseguenza ai ridotti raggi di curvatura, all'elevata memoria elastica e resistenza a flessioni alternate e all'abrasione, sono particolarmente indicate per applicazioni pneumatiche nell'automazione industriale in genere.
TEMPERATURE DI UTILIZZO: Da –20°C a +60°C
COLORI: Su richiesta i tubi possono essere prodotti con colori diversi.

APPLICATIONS: LOW PRESSURE TWIN PU series tubes thanks to their good flexibility and a consequent small bending radius, an high elastic memory and resistance to alternate flexions and to abrasion are specially suitable for pneumatic applications in the industrial automation.
UTILIZATION TEMPERATURES: From – 20°C to + 60°C.
COLOURS:On request, these tubes can be produced in many colours.